

# **Advanced Intelligent Power Solutions**

Setting new standards in data centre management

# **Accessories Summary**

### Temperature Sensor



High/Low temperatures can be set and alerts reported or logged using PDU Agent.

Part No: IPT-500-100

#### Temperature & Humidity Sensor



Part No: IPT-500-200

#### Leak Tape



Part No: IPT-500-900-XX

Leak Tape available in 5mtr incremental lengths or as spot sensors as required. Any alert will be raised.

Daisy chain 8 x Temperature Sensor ports each with separate settings. Units come with 3mtr lead as standard but other lengths available.

> Door or panel sensor as required with alerts sent when contact is broken. If running PDU Agent times would be logged.

#### Door / Panel Sensor



Part No: IPT-500-800

## Daisy Chain Kit



Part No: IPT-500-550

The IPLite units have IO ports to directly daisy chain up to 32 units on 1x IP Address.

For the IT version there is a daisy chain kit available. The IT versions will also support 32 devices on any configuration over a single IP address. Can mix and match any IPower

products on the PDU Agent platform.

#### Camera



Any WEB based camera can be used either stand alone or used in conjunction with the door sensors.

Part No: as specified

Handles with inbuilt or remote key pads connected into the IPower Units. No additional power requirements as release voltage taken from the PDU itself. An array of security access levels and up to 32 separate card users. Alerts can be set and full logging if running PDU Agent. Shown is the Southco version but any Wegan based handle can be incorporated.



as specified

#### Volt Free Contact Port

The volt free contact port can take up to 3 close contact types of sensors against which alerts can be raised.







To EN62368-1:2020 Intertek - 10553241







